

Pilkington **Activ**[™] Cleaning instructions

Maximum visibility. Minimal maintenance.

Pilkington **Activ**[™] uses the UV radiation of daylight to convert the oxygen in the air in such a way that organic pollutants are actively decomposed. Rain then washes the split and dissolved dirt off the outside of the glass. The glass coating ensures that rainwater does not collect in drops, but spreads over the entire surface, giving you a crystal-clear and spotless view.

Initial cleaning after installation

After completion of all installation work, the coated exterior should be rinsed off as quickly as possible with low-lime water to remove all traces of dust and dirt. If the label is still on the outside of the window, please remove it carefully by hand.

IMPORTANT: Avoid – as with any other glass cleaning – using tools and aids such as spatulas, steel wool or razor blades. These can damage the glass surface or the coating. Remove stubborn stains with commercially-available glass cleaners or alcohol. Rubbing down with a shammy leather or using a glass wiper is unnecessary. Simply allow the pane to air dry.

Cleaning objects

Only use soft, clean cleaning cloths or non-abrasive cleaning sponges etc. to clean windows. Glass wipers don't necessarily have to be used but are recommended. When using them, make sure that the rubber lip is clean.

Cleaning agents

In general, all alcohol- and ammonia-based glass cleaners and slightly acidic cleaning agents will suffice and are compatible with Pilkington **Activ**[™]. The cleaning water should be clean and low in lime.



Precautionary measures

When carrying out manual work in the immediate vicinity of your glazing, the glass surface should always be covered. Flying sparks from welding or grinding work can damage the glass. Paints, lacquers, adhesives and mortar products are – as with any other glass – usually difficult to remove.

Cleaning companies

If your glazing will be cleaned by an external company, please draw the attention of the qualified personnel to these special cleaning instructions for Pilkington **Activ**[™].





This publication provides only a general description of the products. Further, more detailed, information may be obtained from your local supplier of Pilkington products. It is the responsibility of the user to ensure that the use of these products is appropriate for any particular application and that such use complies with all relevant legislation, standards, codes of practice and other requirements. To the fullest extent permitted by applicable laws, Nippon Sheet Glass Co. Ltd. and its subsidiary companies disclaim all liability for any error in or omission from this publication and for all consequences of relying on it. Pilkington and "Activ" are trademarks owned by Nippon Sheet Glass Co. Ltd, or a subsidiary thereof.

CE marking confirms that a product complies with its relevant harmonised European Norm. The CE marking label for each product, including declared values, can be found at www.pilkington.com/CE



Pilkington Deutschland AG Hegestraße 45966 Gladbeck, Germany Telefon +49 (0)2043 4 05 56 52 Telefax +49 (0)2043 4 05 56 66 E-Mail: marketingDE@nsg.com www.pilkington.de