



Pilkington **Mirropane™** Chrome Plus Colour
More than just a mirror!

Pilkington **Mirropane™** Chrome Plus Colour – technical performance

Glass product	Light transmittance, LT (%)	4 mm		6 mm		8 mm	
		Light reflectance, outside LR _{out} (%)	Light reflectance, inside LR _{in} (%)	Light reflectance, outside LR _{out} (%)	Light reflectance, inside LR _{in} (%)	Light reflectance, outside LR _{out} (%)	Light reflectance, inside LR _{in} (%)
Pilkington Mirropane™ Chrome Plus Blue	1.0	20	60	20	60	20	60
Pilkington Mirropane™ Chrome Plus Bronze	0.1	27	62	19	62	14	62
Pilkington Mirropane™ Chrome Plus Grey	0.1	23	62	16	62	11	62

Coating on surface #2.

The above performance data has been determined in accordance with EN 410.

The successful silver-coloured Pilkington **Mirropane™** Chrome Plus range has been expanded and now it includes additional three different colours: Grey, Blue and Bronze.

These colours offer a lot of application possibilities and can be used for design installations as well as for functional applications such as partitions, doors or wall claddings.

Pilkington **Mirropane™** Chrome Plus Colour offers a high degree of opacity and outstanding brilliance. Due to its robust properties it is suitable for challenging environments. That means changes in temperature or humidity do not have any impact on the performance of this corrosion resistant product. It can be used for innovative designs for both internal and external applications.

Pilkington **Mirropane™** Chrome Plus Colour offers a wide range of advantages:

- corrosion resistance,
- high opacity,
- can be sandblasted for additional design effects,
- bendable and easy to use,
- easy processing to laminated safety glass and toughened safety glass.

Pilkington **Mirropane™** Chrome Plus Colour is suitable for following areas:

- kitchens,
- bathrooms and wellness areas,
- stylish interior partition,
- partition walls.

Availability:

- Standard thicknesses: 4, 6, 8 and 10 mm.
- Laminated version Pilkington **Mirropane Optilam™** Chrome Plus Colour in thicknesses: 8.8, 10.8, 12.8 and 16.8 mm.
- Standard size 6000 mm × 3210 mm.

Other thicknesses and sizes available on request.



To the fullest extent permitted by applicable laws, Nippon Sheet Glass Co. Ltd. and its subsidiary companies disclaim all liability for any error in or omission from this publication and for all consequences of relying on it.



CE marking confirms that a product complies with its relevant harmonised European Norm.

The Declaration of Performance for each product, including declared values, can be found at www.pilkington.com/CE



Pilkington Group Limited

European Technical Centre
Hall Lane – Lathom Nr Ormskirk L40 5UF – United Kingdom
marketing.communications@nsg.com

www.pilkington.com

March 2021