



Fire-resistant online Glass Enquiry Form

Pilkington **Pyrostop**[®], Pilkington **Pyrodur**[®] & Pilkington **Pyroclear**[®]

Company:		Date :	
Contact:		Tel:	
		E-mail:	

Please use separate forms for different glass types/projects

Project Ref.: <input type="text"/>		Area in total: <input type="text"/> m ²	
Test Report	If known: <input type="text"/> Proj. specific assessment: <input type="checkbox"/> yes / <input type="checkbox"/> no		
Fire resistance classification (EN13501-2)	<input type="checkbox"/> E: Integrity / <input type="checkbox"/> EW: Integrity and reduced heat radiation <input type="checkbox"/> EI: Integrity and Insulation / <input type="checkbox"/> DH: Smoke Barrier		
Resistance Period [min]	<input type="checkbox"/> 30 / <input type="checkbox"/> 60 / <input type="checkbox"/> 90 / <input type="checkbox"/> 120 / <input type="checkbox"/> 180		
Framing Material	<input type="checkbox"/> Wood Type (Soft or Hard Wood): <input type="text"/> or density: <input type="text"/> kg/m ³ Steel: <input type="checkbox"/> Forster / <input type="checkbox"/> Jansen / <input type="checkbox"/> RP Technik / other: <input type="text"/> Aluminium : <input type="checkbox"/> Schüco / <input type="checkbox"/> Reynaers / <input type="checkbox"/> Wicona / other: <input type="text"/>		
Type of Application	<input type="checkbox"/> Fixed Partition / <input type="checkbox"/> Butt-joint / <input type="checkbox"/> Facade / <input type="checkbox"/> Sloped glazing Door: <input type="checkbox"/> single leaf / <input type="checkbox"/> double leaf Window: <input type="checkbox"/> single element / <input type="checkbox"/> multiple elements <input type="checkbox"/> top lite / <input type="checkbox"/> side lite <input type="checkbox"/> Smoke barrier Other: <input type="text"/>		
Type of Installation	<input type="checkbox"/> Internal / <input type="checkbox"/> External		
Technical Specification	<input type="checkbox"/> Monolithic / <input type="checkbox"/> Double glazing / <input type="checkbox"/> Double glazing with blinds (for fixed partition only!) <input type="checkbox"/> Triple glazing U _g -value: <input type="text"/> W/m ² K Light transmission: <input type="text"/> % g-value: <input type="text"/> % Sound reduction: R _w : <input type="text"/> dB; C: <input type="text"/> dB; C _{tr} : <input type="text"/> dB <input type="checkbox"/> Opaque interlayer / <input type="checkbox"/> Irregular shapes (detailed drawings enclosed)		
Glass dimensions width [mm] × height [mm]	<input type="text"/> qty: <input type="text"/>		<input type="text"/> qty: <input type="text"/>
	<input type="text"/> qty: <input type="text"/>		<input type="text"/> qty: <input type="text"/>
	<input type="text"/> qty: <input type="text"/>		<input type="text"/> qty: <input type="text"/>
	<input type="text"/> qty: <input type="text"/>		<input type="text"/> qty: <input type="text"/>
Impact safety performance	<input type="checkbox"/> 1(B)1 / <input type="checkbox"/> 2(B)2 / <input type="checkbox"/> 3(B)3		
Burglar resistance	<input type="checkbox"/> P1A / <input type="checkbox"/> P2A / <input type="checkbox"/> P3A / <input type="checkbox"/> P4A / <input type="checkbox"/> P5A / <input type="checkbox"/> P6B // <input type="checkbox"/> other		
Surrounding wall configuration according to EN 1363-1	<input type="checkbox"/> High density rigid construction e.g. concrete / <input type="checkbox"/> Low density rigid construction <input type="checkbox"/> Plasterboard		
Direction of fire	<input type="checkbox"/> Both sides / <input type="checkbox"/> Inside to outside / <input type="checkbox"/> Outside to inside		

[Submit a form](#)



Pilkington Deutschland AG

Haydnstraße 19 45884 Gelsenkirchen

Tel.: +49 (0)209 1 68 0 Fax: +49 (0)209 1 68 20 56

sales.fire@nsg.com

www.pilkington.com/fireprotection